
OLE HICKORY PITS


Model CTO

WOOD BURNING BARBECUE PITS

QUICK START UP CHECKLIST




1 Make sure switches are off & connect power




6 Check fire box & sliding wood shelf




2 Ensure gas line is connected properly



Add wood to sliding wood shelf



3 Inspect inside



8 Close door




4 Close doors



Power main ON/ Leave C&H OFF



5 Close drain




10 Set temperature

DAILY CLEANING


CLEAN INSIDE OF SMOKER




1 Open door




2 Remove rack & clean with soft bristle brush



3 Spray degreaser



Brush clean with soft bristle brush & rinse




5 Drain grease & remove any meat chunks from bottom

CLEAN OUTSIDE OF SMOKER




6 Wipe off dust, dirt & grease



7 Spray stainless steel cleaner



8 Wipe clean with non-abrasive towel




9 Spray polish




10 Wipe dry with non-abrasive towel

DAILY MAINTENANCE


REMOVE ASH WITH SCRAPER




1 Unplug smoker before maintenance



2 Open fire box & cool



3 Remove wood shelf




4 Clean & avoid getting ashes in burner tube




5 Spray degreaser on gaskets

CLEAN DOOR GASKETS



6 Wipe gaskets clean with non-abrasive towel

DRAIN GREASE



Remove chunks & open valve to drain grease



8 Drain grease into approved container using flex hose




9 Close grease drain




10 Plug in smoker

WEEKLY CLEANING & MAINTENANCE


UNPLUG SMOKER & CLEAN FAN BLADE




1 Locate fan cover




2 Loosen thumb screws



3 Remove cover




4 Remove fan blade with 3/32 T-handle Allen wrench




5 Soak & clean blade & cover


UNPLUG SMOKER & CLEAN FAN BLADE




6 Clean cover with soft bristle brush




7 Install fan blade w/ 3/32 T-handle, hub faces away from motor



8 Install cover



9 Tighten thumb screws




Remove ash with ash shovel


CLEAN SENSOR PROBES



11 Inspect burner tube with mirror & remove ash




12 Spray cleaner carefully



13 Use soft bristle brush to clean probes



Insert flue brush all the way down to handle to remove build up



Clean both flue pipes frequently